

PARAMETERS ▶ ▼ PRODUCTS	TRANSMISSION CHANNEL	CONTACT INPUTS	RELAY OUTPUTS	PHONE NUMBERS FOR NOTIFICATION	NUMBER OF USERS	EVENT LOGS	OUTPUT CONTROL BY FREE CALL	NOTIFICATIONS				MOBILE APP IOS/ANDROID	IP CAMERA SUPPORT	POWER SUPPLY	REMOTE MANAGEMENT	DESKTOP APPLICATION	APPLE WATCH / CARPLAY ⁽⁸⁾ COMPATIBILITY	GOOGLE HOME / ALEXA COMPATIBILITY	SIM CARD TYPE
								SMS	CALL	E-MAIL	PUSH								
GSM GATE AUTOMATION																			
Gate Control BASE 1000 – 4G.IN4.R2	4G / 2G	4	2	4	1000 / Unlimited ⁽²⁾	✓	✓	✓	✓	–	–	–	–	U ⁽⁶⁾	Internet / SMS	✓	–	–	2FF
Gate Control BASE 1000 DIN rail – 4G.IN4.R2	4G / 2G	4	2	4	1000 / Unlimited ⁽²⁾	✓	✓	✓	✓	–	–	–	–	U ⁽⁶⁾	Internet / SMS	✓	–	–	4FF
Gate Control PRO 20 – 4G.IN4.R2	4G / 2G	4	2	4 / Any User ⁽¹⁾	20 / Unlimited ⁽³⁾	✓	✓	✓	✓	✓	✓	✓	✓	U ⁽⁶⁾	Internet	✓	–	–	2FF
Gate Control PRO 20 DIN rail – 4G.IN4.R2	4G / 2G	4	2	4 / Any User ⁽¹⁾	20 / Unlimited ⁽³⁾	✓	✓	✓	✓	✓	✓	✓	✓	U ⁽⁹⁾	Internet	✓	–	–	4FF
Gate Control PRO 1000 – 4G.IN4.R2	4G / 2G	4	2	4 / Any User ⁽¹⁾	1000 / Unlimited ⁽³⁾	✓	✓	✓	✓	✓	✓	✓	✓	U ⁽⁶⁾	Internet	✓	–	–	2FF
Gate Control PRO 1000 DIN rail – 4G.IN4.R2	4G / 2G	4	2	4 / Any User ⁽¹⁾	1000 / Unlimited ⁽³⁾	✓	✓	✓	✓	✓	✓	✓	✓	U ⁽⁹⁾	Internet	✓	–	–	4FF
GSM/IP GATE AUTOMATION																			
Gate Control PRO 1000 Monitoring DIN rail – ETH.4G.IN4.R2	LAN / 4G	4	2	4 / Any User ⁽¹⁾	1000 / Unlimited ⁽³⁾	✓	✓	✓	✓	✓	✓	✓	✓	U ⁽⁹⁾	Internet	✓	–	–	4FF
“SMART” GATE CONTROL																			
OPEN.ioting	LAN / Wifi	3 ⁽⁴⁾	2	–	50 (free) / 100 / 500	✓	–	–	–	–	✓	✓	–	U ⁽⁷⁾	Mobile app	–	✓	✓	–
OPEN.ioting Power+	LAN / Wifi	3 ⁽⁴⁾	2	–	50 (free) / 100 / 500	✓	–	–	–	–	✓	✓	–	U ⁽⁹⁾	Mobile app	–	✓	✓	–

⁽¹⁾ Notifications can be configured for each user separately.

⁽²⁾ Anyone can control an output via private call (with hidden caller ID).

⁽³⁾ Anyone can control an output by via private call (with hidden caller ID) or via normal call, if enabled in the group rule settings.

⁽⁴⁾ Dedicated inputs for limit switches and for contact-based control with an external device.

⁽⁵⁾ 12-30V AC/DC

⁽⁶⁾ 12-30V DC / 12-16,5V AC

⁽⁷⁾ 85-265V AC / 48V PoE

⁽⁸⁾ Limited support: a control button is placed on the interface, and voice control is also possible.

⁽⁹⁾ 12-30V DC / 12-24V AC

PARAMETERS ▶ ▼ PRODUCTS	POWER	OUTPUT VOLTAGE	BATTERY CHARGING
POWER SUPPLIES			
TT40VA-12V5	40VA	12.5V	✓